

To whom it may concern:

Certificate of conformity Jupiterseal type P/UM-280

The object of the declaration described above — boxes of corrugated board, layer for direct contact with food-is in conformity with the requirements of the following documents:

Document Nr.	Name	Reference
<i>IST 110012450-29.2019</i>	<i>Boxes of corrugated board</i>	<i>2.29-12-2019</i>
<i>JST 110012450-31.2019</i>	<i>Corrugated board</i>	<i>2.01-03-2019</i>
<i>1935 /2004</i>	<i>Regulation (EC)No 1935/2004 of the European Parliament and of the Council of 27 October 2004 on materials and articles intended to come into contact with food and repealing Directives 80/590/EEC and 89/109/EEC</i>	<i>27- 10- 2004</i>
<i>HN 16-2011</i>	<i>Hygiene Norm HN 16:2011 "Materials and articles intended to come into contact with food, special health safety requirements"</i>	<i>07-05- 2011</i>

Additional information:

Given corrugated cardboard is made from these papers – kraftliner / fluting / testliner.

Overall Migration of Lead, Cadmium, Mercury, Hexavalent Chromium and Polychlorinated Biphenyls does not exceed the permissible limits specified in HN 16:2011. Annex - testing protocol No. Ch 6421 (03-08-2018, Chemical Testing Department of National Public Health Surveillance Laboratory)

To whom it may concern:

Certificate of conformity Jupiterseal type P/UM-280

Specification:

Nr.	Qualitative indicators	Grade	Norm	Test methods
1.	Internal dimensions, mm	C70RKT		
2.	g/m²	473		LST EN 20287
3.	Burst-Bending crush, kPa (BST)	950		ISO 2759
4.	Edge crush, kN/m (ECT)	5,0		LST EN ISO 3037

Composition:	kraftliner	fluting	testliner	
Recycled content %	74			

Given material is 100% recyclable

Multipakend Tootmine OÜ provides a 12-month guarantee for the mechanical durability and visual quality of our corrugated board and its products, starting from the production date. This guarantee is subject to the following conditions, ensuring that the corrugated board and its products are stored and transported in accordance with the following requirements:

1. Transportation: The corrugated board and its products must not incur any mechanical damage during transportation.
2. Storage: The products should be stored in the original packaging as provided by the producer.
3. Storage Temperature: The storage temperature should be maintained between +5°C and +35°C.
4. Relative Air Humidity: The relative air humidity in the storage area should be maintained within the range of 40% to 70%.
5. Protection from Water: The corrugated board products must not be directly exposed to water.
6. Prevention of Water Condensation: Water condensation should not be allowed to form on any walls of the boxes.
7. Timely Unpacking: Pallets of corrugated board boxes should be unpacked directly before use and not stored for an extended period.
8. Protection from Direct Sunlight: It is crucial to store the corrugated board boxes away from direct sunlight. Prolonged exposure to sunlight can result in potential discoloration or degradation of the packaging materials. Therefore, it is strongly advised to store the boxes in shaded areas and indoors, ensuring they are protected from direct sunlight.