

856SFR Cushion Ease Solid™ GSII® Nitrile FR

Nitrile FR GSII® modular mat



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting 856SFR Cushion Ease Solid™ GSII® Nitrile FR

Ergonomic benefit derived from a 19 mm thick worker platform with a closed anti-slip pebble structure surface for maximum anti-fatigue comfort in dry industrial environments.

- Heavy duty rubber tiles can be easily assembled for coverage of large areas or individual workstations, wall-to-wall or as islands
- With abrasive Grip Step® coating for extra adherence in extremely slippery areas
- Compatible with patented MD Ramp System™ for smart safety bevelling solutions; allows outside and inside corners
- Resistant to most industrial oils and suitable for welding areas

Recommended use

- Wet/Dry and Oily Areas
- For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
- Heavy duty

Colors:

- Black

Sizes:

- 91cm x 91cm
- per m2

Accessories:

- 552 MD-X Ramp System™ Nitrile
- INS INSTALLATION
- 651 M.D. Fire Retardent Ramp System
- 551 MD Ramp System™ Nitrile



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE

Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Modular Matting Cushion Ease Solid™ GSII® Nitrile FR

General

Brand	Notrax
Category	Dry Areas Modular Matting
Product Number	856SFR
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Cushion Ease Solid™ GSII® Nitrile FR
Recommended use	For placement in manufacturing plants, production lines, assembly lines, CNC machines, metal working for individual workstations and custom work platforms
Series	Cushion-Ease®
Shipping Location	Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States
Type	Dry Areas - Heavy Duty Modular Rubber Mats
Update trigger	20210310-1301
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Reach US	Not REACH Compliant
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty	1

Tests

Abrasion Resistance 1000	2.3% (5000 cycles)
Fire rating EU	EN 13501-1 Bfl-S1
Fire rating US	Pass
Slip Rating	R10
Coefficient Friction Dry	0.86
Surface Flammability	Pass

Technical Specifications

Application	Industrial Environments
Edges	Attachable bevelled edges are available
Material	100% nitrile fire retardant rubber compound
Material Group	Nitrile rubber
Process	Compression Moulding

Art. nr.	Dimension (cm)	Weight (kg)	Height (cm)
856SFR00BL	per m2	13.9	1.9
856SFR33BL	91cm x 91cm	13	1.9

Accessories

552 MD-X Ramp System™ Nitrile	INS INSTALLATION	651 M.D. Fire Retardent Ramp System	551 MD Ramp System™ Nitrile
-------------------------------	------------------	-------------------------------------	-----------------------------