

Technical Datasheet ABS 08200003

Type	ABS
Length L	3000 mm
Length of lip	150 mm
Total width	230 mm
Internal Width Dimension B	155 mm
Weight/piece	11 kg

Max. capacity specified in daN per ramp:

for vehicles with two axles with

Axle load distribution 40% to 60%

Capacity at axle distance 0,75 mtrs	165 daN(kp)
-------------------------------------	-------------

Capacity at axle distance 1,00 mtrs	175 daN(kp)
-------------------------------------	-------------

Capacity for one axle vehicle	130 daN(kp)
-------------------------------	-------------

max. height difference at 30% HDmax	810 mm
-------------------------------------	--------

max. height difference at 20% HDmax	560 mm
-------------------------------------	--------

min. height difference HDmin	450 mm
------------------------------	--------

including slip off safety device	Square plate
----------------------------------	--------------

Height of construction	48 mm
------------------------	-------

Height of curb	43 mm
----------------	-------

Running surface	Groove
-----------------	--------

according to drawing	110.1838
----------------------	----------

aid registration number	22.50.01.0030
-------------------------	---------------

Made in Germany

GS-proved

These ramps are not suitable for driving on

directly with steel tracked vehicles. Please put a

working part (wood) between ramp and steel track.