

**ALTEC GmbH**

Rudolf-Diesel-Straße 7
D-78224 Singen

Telefon: 0 77 31/87 11-0
Telefax: 0 77 31/87 11 11

Internet: www.altec.de
E-Mail: info@altec.de

ALTEC GmbH · Rudolf-Diesel-Straße 7 · D-78224 Singen

Technical Datasheet AOS 08101008

Type	AOS_200
Version	without curb
Type of connection/support	Lip 155
Length L	1505 mm
Total width	205 mm
External width dimension B	200 mm
Internal Width Dimension B	200 mm
Height of construction dim. H	60 mm
Weight/piece	6 kg
Max. capacity specified in daN per ramp:	
for vehicles with two axles with	
Axle load distribution 40% to 60%	
Capacity at axle distance 0,75 mtrs	365 daN(kp)
Capacity at axle distance 1,00 mtrs	435 daN(kp)
Capacity for one axle vehicle	235 daN(kp)
max. height difference at 30% HDmax	400 mm
min. height difference HDmin	230 mm
Running surface	perforated
including slip off safety device	yes
including steel pin safety device	yes
according to drawing	110.4069

Made in Germany

These ramps are not suitable for driving on
directly with steel tracked vehicles. Please put a
working part (wood) between ramp and steel track.