

COLLECTING CONTAINER **TYPE ASB**



ASB 450-I



ASB 250

For the international transport of hazardous liquids according to ADR/RID and the IMDG code, collection and storage of flammable liquids of GHS-categories 1 - 3

- outer container serves as a containment sump with lid
- lockable lid with gas compression springs
- inner tank (screwed to outer)
- fill hole Ø 400 mm
- funnel and stainless steel sieve
- dipstick to register any leakage
- pressure relief valve ¾"
- suitable for pick-up by a pallet truck, forklift or crane
- can be used indoors or outdoors
- max. density 1.8 kg/l

Accessories

- fill or suction pipe with 2" coupling, threaded coupling and cap
- inner tank with sump under suction pipe
- 1" threaded coupling with plug
- embossed company name

Finish		
	Inner tank 4 mm	Outer tank 2 mm
1.	hot-dip galvanized	hot-dip galvanized
2.	stainless steel	hot-dip galvanized
3.	stainless steel	stainless steel

UN-APPROVALS	
	31A/Y/D/BAM 0137-0142-BAUER/4000

	Volume in l	No. of inner tanks x litre	Dimensions (l x w x h) in mm	Can be stacked	Weight in kg
ASB 250	250	1 x 250	800 x 815 x 830	3 high	200
ASB 450-I	450	1 x 450	1210 x 885 x 830	3 high	290

Finish:

hot-dip galvanized

stainless steel