

product specification


Manutan code:	A682395
Vendor code:	5028S
Description:	Stand with 6 hooks
Overall size:	H1800 x W410 mm
Color:	black
N.Weight:	9300 g



Key Parts Specification


Hook

material:	ABS
size:	70×95×170 mm
Color:	matt black




Fixture

material:	Iron
ring:	Ø220×H50×T3.0 mm , power coated, black (Ral9004)
tube:	Ø40×T1.2×90 mm , power coated, black (Ral9004)
	Ø12×T1.0×85 mm



Upper pole

material:	iron
size:	Ø40×T1.2×L820 mm
Finish:	power coated, black (Ral9004)




Lower pole

material:	iron
size:	Ø40×T1.2×L820 mm
Finish:	power coated, black (Ral9004)




Holder

material:	ABS
size:	Φ280×35 mm
Color:	matt black



Basement

material:	ABS
size:	Φ365×40 mm
Finish:	matt black



Accessories

screw (G)	M4×L10 mm
washer (I)	Φ44×Φ12.5×T7 mm
nut(K)	M4 , 2 PCS
washer (m)	M8 screw through
Pole (H)	M8×55 MM
screw (J)	M4×L30 mm
Bolt (L)	M8×L50 mm
wrench (N)	the open size 14 mm

 G*12	 I*1	 K*2	 M*1
 H*1	 J*2	 L*1	 N*1

Logo

Clear sticker with logo

product label 5cm*3cm



Sticker at Yellow position

Assembly instruction



A682395 5028S assembly instruction rev12.17.pdf

Key Factors

1.aesthetics check

No obvious defects on powder coating and plastic to naked eyes.

Any place which persons may contact shall be free of sharp edges, sharp angles ; The gloss and color should be uniform ; The surface should be clean, no visual fingerprints and scratches .

2. assembly check

Check all parts quantities and assembled all parts according to assembly instruction , make sure every part to match its specification , all parts can assembled together proper , take the product on the flat ground , no swing as a arm holding the pole and applying forces ; watching from different views , no obvious tip ; no move occurrence by touching any part .

3.static load for hanger

A 50N force is loaded on every hangers for 24H,the test result should meet requirement as below

3.1 there are no fractures of any member, joint or component.

3.2 there are no loosening of joints intended to be rigid.

3.3 no major structural element is significantly deformed.

3.4 can't make a overturn.

4.Adhesion test of powder coating

Use a tape of 3M250 to directly stick the powder surface, rapidly split it off having a 90° with test surface , no peel off.

Shipping mark



A682395 3665867080588 rev12.17.pdf

Packing

1 pc / carton

